

# INSULATED/REFRIGERATED

## Fresh Max Heavy Duty



### THE BEST INSULATION WITH ALL THE OPTIONS, FEATURES AND SIZES YOU NEED

Maximum insulation and temperature control along with smoother, flatter interior and exterior walls. Foam is injected in temperature controlled press that helps provide you with the maximum foam expansion along with flat interior and exterior walls.

#### SPECIFICATIONS

Available lengths

10' to 28'

Available heights

79' to 104'



# Special Features and Options



## STANDARD

- Floors – Extruded Aluminum “Hat”, “T”, “Inverted T”, 1/8" Aluminum treadplate. Subfloor: 3" I-Beam crossmembers on 12" c/l, 4" I-Beam long sills.
- Sidewalls, Front wall – .040 Prepainted white aluminum panels with “Z” posts, side posts on 16" c/l.
- Roof – .032 Aluminum roof, one piece. Anti-sag, crowned roof bows on 24" c/l.
- Rear frame – Galvanealed steel, 12 gauge steel perimeter with 10 gauge sill painted white. Full width rain gutter at top rear header.
- Interior lining – One piece seamless Kemlite sidewalls and ceiling.
- 3" urethane foam sidewalls, ceiling, 4" urethane foam floor and front wall.

## OPTIONS

- Stainless steel rear frame.
- Seamless fiberglass exterior panels.
- Doors – Whiting 1-1/2" and 2-1/2" insulated overhead doors; Full opening swing; Two panel, Three panel, Four panel swing. Single and Two panel narrow opening. Single panel swing side doors.
- Insulation: 4" and 5" throughout
- Liftgates: tuckaway and railgates per specification
- Thermo King and Carrier engine driven and self contained units available upon request
- Cargo control – E track

[www.completetruckbodies.com](http://www.completetruckbodies.com)

**Complete**  
Truck Bodies, Inc

**800-345-6153**